

ZT-4400TM

REVOLUTIONARY HYDRAULIC DESIGN

- ⚙️ Heavy-duty commercial grade transaxle
- ⚙️ Industry leading 1- $\frac{3}{8}$ inch axle for heavier loads
- ⚙️ High capacity thrust bearing for longer life
- ⚙️ Designed to fill the gap—perfect for machines up to 1800 lbs



HYDRO-GEAR[®]
COMMERCIAL

DESIGNED & ASSEMBLED IN THE USA

ENGINEERED TO PERFORM

SPECIFICATIONS

Pump Displacement	0.73 in³/rev [12 cc/rev]
Motor Displacement	0.97 in³/rev [16 cc/rev]
Input Speeds	
Max Hi-idle (No Load)	3600 rpm
Min (Loaded)	1800 rpm
Output Torque	up to 575 lb-ft [up to 780 Nm]
Speed	up to 12 mph [up to 19 kph]
Gross Vehicle Weight	up to 1800 lbs [up to 816 kg]
Axle Shaft Diameter	1.375 in [35 mm]
Axle Shaft Options	Tapered 4 or 5 bolt Flange
Weight of Unit	55 lbs [25 kg]

Specifications subject to change without notice

**FOR MORE INFORMATION VISIT:
WWW.HYDRO-GEAR.COM**



ZT4400-10/2017-V1